

# PracticeVCE

## Pass Your Next Certification Exam Fast!

Everything you need to prepare, learn & pass your certification exam easily.

365 days free updates. First attempt guaranteed success.

15+  
YEARS IN BUSINESS

39795+  
SUCCESSFULL CASES

39305+  
SATISFIED CLIENTS

39395+  
THE NUMBER OF CONSULTING

## TRY BEFORE YOU BUY

Download a free sample of any of our exam questions and answers

- ✓ 24/7 customer support, Secure shopping site
- ✓ Free One year updates to match real exam scenarios
- ✓ If you failed your exam after buying our products we will refund the full amount back to you.



### 365 Days Free Updates

Free update is available within 365 days after your purchase. After 365 days, you will get 50% discounts for updating.



### Security & Privacy

We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.



### Instant Download

After Payment, our system will send you the products you purchase in mailbox in a minute after payment. If not received within 2 hours, please contact us.



### Money Back Guarantee

Full refund if you fail the corresponding exam in 60 days after purchasing. And Free get any another product.

<http://www.practicevce.com>

Professional Study Tool and Reliable Exam Practice Material

**Exam :** 920-136

**Title :** NCDS - Ethernet Switching Solutions

**Vendors :** Nortel

**Version :** DEMO

NO.1 An engineer implemented a core network consisting of four Ethernet Routing Switch 8600s and needs the ability to build a redundant core. Which feature would be used to provide redundancy and fail-over times?

- A. Spanning Forest
- B. Multi-Link Trunking
- C. Protocol Based VLANs
- D. Split Multi-Link Trunking

Answer: D

NO.2 A carrier needs to support OC-12c (STM-4) and OC-3c (STM-1) on an Ethernet Routing Switch 8600.

What is a minimal configuration needed to support this requirement?

- A. one ATM module and no MDAs
- B. one OC-12c/STM-4 module and one OC-3c/STM-1 module
- C. one OC-12c/STM-4 ATM MDA and one OC-3c/STM-1 ATM MDA on an ATM module
- D. one OC-12c/STM-4 ATM MDA on the first ATM module and one OC-3c/STM-1 ATM MDA on the second ATM module

Answer: C

NO.3 A customer is connecting a new remote office to the corporate network. The office will be connected to the network core through a fiber link that terminates at an Ethernet Routing Switch 8600 almost 40km away. It will provide 10/100 Ethernet access for ten people, two printers and one file server at the remote location. The switch that will be installed must meet the requirements below. The switch must support IEEE 802.3af Power over Ethernet. Differentiated Services (DiffServ) and advanced IP Policies must be supported to provide IP QoS. The switch must support the 1000Base-XD Gigabit Interface Connector (GBIC) or Small Form-Factor Pluggable (SFP GBIC) for the uplink connection. Which switch meets these requirements?

- A. Ethernet Switch 425-24T

- B. Ethernet Switch 470-48T
- C. Ethernet Routing Switch 1648T
- D. Ethernet Switch 460-24T-PWR

Answer: D

NO.4 A customer is adding fiber support onto an existing 48 port 5510. Their current installation is using all UTP ports on the switch. They need to install two 1000 Base-SX SFPs into the SFP slots. Which

statement is true about the requirements for this installation?

- A. The Console port requires SFPs.
- B. Only one 1000 Base-SX GBIC will be supported.
- C. It will require ports 47 and 48 to be unplugged before using SFPs.
- D. It will require the power to the unit is turned off before installing GBICs.

Answer: C

NO.5 Internet Group Management Protocol (IGMP) is used by IP Multicast routers to learn about the existence of host group members on their directly attached subnets. Which statement about IGMP is true?

- A. The IP Multicast routers get this information by listening for IP hosts broadcasting IGMP queries and reporting their host group memberships.
- B. The IP Multicast routers get this information by broadcasting IGMP queries and listening for IP hosts reporting their host group memberships.
- C. The IP Multicast routers get this information by recognizing the modified MAC address of a Multicast packet and adding that MAC address to the Multicast tree.
- D. The IP Multicast routers get this information by listening for Multicast Servers broadcasting IGMP queries and listening for IP hosts reporting their host group memberships.

Answer: B

NO.6 A customer is selecting an Ethernet Routing Switch to be used to route legacy protocols. It must be able to route IPX traffic and dynamically advertise IPX routes in a network. Which Ethernet

## Routing

Switch will meet these requirements?

- A. 1600
- B. 5500
- C. 8300
- D. 8600

Answer: D

NO.7 A customer is selecting an Ethernet Routing Switch to be installed in a wiring closet.

The switch must

support 10 Gbps connections and have redundant power. Which two Ethernet Routing Switches will meet

these requirements? (Choose two.)

- A. 1600
- B. 5520
- C. 5530
- D. 8600

Answer: CD

NO.8 A customer is implementing video conferencing devices that require Power over Ethernet (PoE). They

are planning to use an Ethernet Routing Switch 8310 chassis for this deployment. They would also like to

install 8600 modules in the chassis. Which statement about this customer scenario is true?

- A. Both PoE and 8600 modules are supported in the 8310 chassis.
- B. Neither PoE or 8600 modules are supported in the 8310 chassis.
- C. 8310 chassis does not support PoE, but will support 8600 modules.
- D. PoE could be supplied via the 8310 chassis, but will not support 8600 modules.

Answer: D

NO.9 A customer is expressing concern about reliability for their single uplink connection to the wiring closet.

The switches in the wiring closet support Distributed Multi-Link Trunking (DMLT). What can be done so

the Ethernet Routing Switch 8600 can eliminate a single point of failure for the lowest price?

- A. Add a second switch fabric module.
- B. Duplicate the trunk elements in software.
- C. Duplicate the trunks across separate modules using DMLT.

D. Configure multiple Ethernet Routing Switch 8600s using Split Multi-Link Trunking (SMLT).

Answer: C

NO.10 A customer has a stack of Ethernet Switch 470-48Ts. The uplinks to the network core are via two

Gigabit uplink ports from the first Ethernet Switch 470-48T in the stack to a single Ethernet Routing Switch

8600. The links are not part of a MultiLink Trunk (MLT), and spanning tree is running. This results in one

of the links always being blocked and recovery time unacceptably long when the active uplink fails. They

need to have both links active to increase the bandwidth to the core, and at the same time provide better

redundancy. What is the preferred Nortel solution for the customer?

A. Move one of the uplinks to another Ethernet Switch 470-48T in the stack and disable spanning-tree on both uplinks.

B. Move one of the uplinks to another Ethernet Switch 470-48T in the stack and enable Equal Cost Multi-Path (ECMP) on the uplinks.

C. Move one of the uplinks to another Ethernet Switch 470-48T in the stack, and group the two uplinks in a Distributed MultiLink Trunk (DMLT).

D. Move one of the uplinks to another Ethernet Switch 470-48T in the stack, and ensure that the two uplinks terminate on different modules in the Ethernet Routing Switch 8600.

Answer: C